

AMENDMENT

Amendments to the Claims

- 5b7  
D
1. (currently amended): A system for call processing, comprising:
- a telephone call receiving switch configured prior to answering a call to detect and pass out of band call destination information;
  - an IVR adapted to perform an audio script, said IVR in electronic communication with said switch;
  - a server computer in electronic communication with said telephone call receiving switch for receiving the out-of-band call destination information and in electronic communication with said IVR for forwarding the out-of-band call destination information to said IVR;
  - a network structure in electronic communication with said IVR and said server; and
  - a port sharing data interface processing (DIP) program in operation with said IVR, said program adapted to enable said script to be performed on multiple ports of said IVR.
- C
2. (original): The system of claim 1, wherein the DIP dynamically allocates scripts to ports.
3. (original): The system of claim 1, wherein the system manages port state before, during, and after a call.
4. (original): The system of claim 1, wherein a single list of DNIS numbers resides at said IVR.
5. (previously presented): A system comprising:
- a plurality of telephone call receiving switches, each configured prior to answering a call to detect and pass out of band call destination information;
  - a plurality of multiple port IVR's adapted to play a plurality of scripts, in electronic communication with said switches;

at least one server computer in electronic communication with said plurality of telephone receiving switches for receiving the out-of-band call destination information and in electronic communication with said IVR's, said at least one server configured to associate one of said plurality of scripts to the out-of-band call destination information;

a network structure facilitating electronic communication between said IVR's and said switches and said at least one server; and

a port sharing data interface processing program in operation with IVR's, whereby each port of each IVR is monitored to determine its availability to receive a call, to request call destination information from said server via said network structure and play at least one of said scripts to a caller.

6-9. (canceled).

10. (previously presented): A system for call processing, comprising:

a telephone call receiving switch configured to detect call destination information of an incoming call, to assign the incoming call to a selected one of a plurality of channels, to pass the call destination information out of band to the selected channel, and to answer the incoming call;

a table containing a plurality of call destination records associated with a plurality of applications;

a server apparatus in data communication with said switch and said telephone call receiving switch and responsive to the out of band call destination information to identify an associated application with reference to the table and to a call identifier to the incoming call;

an IVR that includes a port in telephony communication with the selected channel and in data communication with the server, the IVR including a port sharing data interface processing program responsive to the detected call destination information and incoming call reaching said port to access said associated program to perform on the selected port.

11. (previously presented) The system of claim 10, wherein the telephone call receiving switch is further configured to detect call origination information of the incoming call, wherein the application comprising an audio script, the system further comprising:  
a scripter configured to prepare a script responsive to said call origination information.

C1  
12. (previously presented): The system of claim 1, wherein said telephone call receiving switch is further configured to detect and pass out of band call destination information by detecting comprising Dialed Number Identification Service (DNIS) and Automatic Number Identification (ANI) associated with the call.

---